

In the Claims

1. (currently amended) A trim panel insulator for a vehicle, [comprising] consisting essentially of:
 a single, nonlamine acoustical and thermal insulating layer of polymer fiber selected from a group consisting of polyester, a combination of polyester and fiberglass, polypropylene and any mixtures thereof.

2. (canceled)

Lab
AM
3. (currently amended) The insulator of claim [3] 1, including a first facing over a first face of said acoustical and thermal insulating layer, said first facing layer being constructed from a material selected from a group consisting of polyester, rayon, polyethylene, polypropylene, ethylene vinyl acetate, polyvinyl chloride, fibrous scrim, metallic foil and mixtures thereof.

4. (currently amended) The insulator of claim [4] 3, including a second facing layer over a second face of said acoustical and thermal insulating layer.
 LAB

5. (currently amended) The insulator of claim 4, wherein said acoustical and thermal insulating layer has a [density] weight per unit area of between about 20-130 g/ft².

claiming one layer

6. (original) The insulator of claim 5, wherein said acoustical and thermal insulating layer and said first facing layer are approximately the same color.

LAB

7. (original) The insulator of claim 5, wherein said acoustical and thermal insulating layer, said first facing layer and said second facing layer are approximately the same color.

LAB

LAB

3 layers

8. (re-presented - formerly dependent claim 2) A trim panel insulator for a vehicle, comprising: a single, nonlaminated acoustical and thermal insulating layer of polymer fiber selected from a group consisting of polyester, a combination of polyester and fiberglass, polypropylene and any mixtures thereof also including a nonlaminated skin of polymer fiber along at least one face of said acoustical and thermal insulating layer, said nonlaminated skin having a higher density than a remaining portion of said insulating layer.

AM

9. (new) The insulator of claim 8, including a first facing layer over a first face of said acoustical and thermal insulating layer, said first facing layer being constructed from a material selected from a group consisting of polyester, rayon, polyethylene, polypropylene, ethylene vinyl acetate, polyvinyl chloride, fibrous scrim, metallic foil and mixtures thereof.

10. (new) The insulator of claim 9, including a second facing layer over a second face of said acoustical and thermal insulating layer.

11. (new) The insulator of claim 10, wherein said acoustical and thermal insulating layer has a weight per unit area of between about 20-130 g/ft².

12. (new) The insulator of claim 11, wherein said acoustical and thermal insulating layer and said first facing layer are approximately the same color.

Am

13. (new) The insulator of claim 11, wherein said acoustical and thermal insulating layer, said first facing layer and said second facing layer are approximately the same color.